

## EVC | 7.5 MM, 20 MIL

Construction	Expanded Polymer Core, EVC
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	5.75" Wide x 48" Long
Overall Thickness	7.5 mm (includes 2 mm Pad)
Attached Pad	2 mm Pad
Wear Layer	20 mil
Finish Coat	Super Protect Low Gloss
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	15.3 sf/ctn, 84 ctn/pal, 1285.2 sf/plt, 27 lbs/ctn

### Installation & Maintenance

Angle / Angle

Expansion & Transition: 1/4" Expansion required at perimeter and at all vertical surfaces.  
Transition required for rooms larger than 26' W x 36' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor


### Test Method & Requirements

Resilient Floor in Modular Format	ASTM F3261	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass
Determination of Geometrical Characteristics	ISO 24337	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

\*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

### Health & Environmental

FloorScore SCS Certified  
Phthalate-Free



### Warranty


10 Year Commercial, 10 Year Multi-Family, 30 Year Residential

### Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round

[QNoise](#) Stair Nosing

### Layout Options:



ASHLAR



STAGGER