

# TANDEM TILE



EVC | 7,5 MM, 20 MIL



**Castell** | WIWP0201



**Scotney** | WIWP0205



**Pearl** | WIWP0203



**Whisper** | WIWP0202



**Heather** | WIWP0204

## SPECIFICATIONS

Construction	Expanded Polymer Core, EVC
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B
Dimensions	12" Wide x 24" Long
Overall Thickness	7.5 mm (includes 2 mm Premium Pad)
Wear Layer	20 mil
Finish Coat	Low Gloss Polyurethane
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	19.80 sf/ctn, 48 ctn/pal, 950.4 sf/plt, 31.5 lbs/ctnl
Installation	Angle/Drop/Tap
Warranty	10 Yr Commercial, 10 Yr Multi-Family, 30 Yr Residential

## INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Relative Humidity: 30% - 50%
- Acclimation: 24 hrs in carton
- Room Temperature: 70°F
- Expansion Space: 1/4" around perimeter
- Use T-Mold in spaces larger than 25' l x 35' w
- Inspect flooring prior to installation
- Use floor protection for furniture

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**



Additional specifications, full installation/maintenance and warranty information available online at [TASCONTRACT.COM](https://TASCONTRACT.COM).



**TAS** supply company, Inc.