

EXPEDITION



GLUE DOWN | 2.0 MM, 12 MIL



Artic | IMLV0301



Hudson Bay | IMLV0307



Cape Horn | IMLV0305



Patagonia | IMLV0304



Magellan | IMLV0306



Cortez | IMLV0302



Fjord | IMLV0308



Spice Road | IMLV0303

SPECIFICATIONS

Construction	Solid Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions	6" Wide x 48" Long
Overall Thickness	2.0 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Square Edge
Packaging	35.96 sf/ctn, 78 ctn/pal, 2804.9 sf/plt
Installation	Glue Down
Warranty	5 Yr Light Commercial, 5 Yr Multi-Family, 20 Yr Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Gypcrete Substrates

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
QNOSE**

