

# ODYSSEY EIR

## PRODUCT SPECIFICATIONS



### Product Specifications

Type	
Construction	Layered plank consisting of Eco Protec antimicrobial coating, wearlayer, film, 2 stabilization cores, and backing
Classification	ASTM F1700, Class III, Type B - Solid Vinyl Floor Tile/Plank
Wearlayer	Polyurethane/Ceramic Bead
Wearlayer Thickness	20mil
Size	7.25" width x 48" length
Overall Thickness	3mm
Square Feet Per Carton	34.96
Cartons Per Pallet	50
Weight Per Carton	40 lbs

Installation	
Glue Down Adhesive: Residential & Multi-Family - WF Taylor Dynamic	
Glue Down Adhesive: Commercial - WF Taylor Pinnacle	

Warranties	
Lifetime Limited Residential, 15 Yr Commercial, 15 Yr Multi-Family	

Test Method & Requirements		
Solid Vinyl Floor Tile	ASTM F1700	Class III, Type B
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wearlayer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM F2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Smoke Density	ASTM E662	Meets

Additional Specifications, Full Installation Instructions & Warranty Information Available at [www.tasflooring.com](http://www.tasflooring.com) | a division of **T&A supply company, inc.**