



Mead | DJLV0101



Grove | DJLV0102



Arden | DJLV0103



Cadet | DJLV0104



Coffee | DJLV0105



Java | DJLV0106



Kelso | DJLV0107



Norse | DJLV0108

SPECIFICATIONS

Construction	Solid Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long
Overall Thickness	2.5 mm
Wear Layer	20 mil
Finish Coat	Polyurethane Glass Bead
Texture	Embossed
Edge Profile	4-Sided Square Edge
Packaging	42.03 sf/ctn, 50 ctn/plt, 2101.5 sf/plt
Installation	Glue Down
Warranty	15 Yr Commercial, 15 Yr Multi-Family, Limited Lifetime Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Gypcrete Substrates

Read Complete Instructions Before Installing



**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**
[QNOSE](#)

tascontract.com

