

# CATALYST

**TAS**  
FLOORING

SPC | 4.5 MM, 12 MIL



**Regis** | RCRC0201 \*



**Midfield** | RCRC0202




**Langston** | RCRC0203



**Seacliff** | RCRC0204



**Collins** | RCRC0205



**Hermes** | RCRC0206 \*



**Saturn** | RCRC0207



**Zeus** | RCRC0208 \*



**Hera** | RCRC0209



**Atlas** | RCRC0210



**Athena** | RCRC0211



**Eros** | RCRC0212

\*Non-Stock Colors  
Available through our  
Platforms Program.  
Minimum QTY Applies.

## SPECIFICATIONS

Construction	Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7" wide x 48" long
Overall Thickness	4.5 mm
Wear Layer	12 MIL
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	26.049 sf/carton - 42 carton/pallet - 1094.058 sf/pallet
Installation	Angle/Drop & Tap
Warranty	5 Year Light Commercial, 5 Year Multi-Family, 25 Year Limited Residential Warranty

## INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 3/16" in 10'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing



**SPEC SHEET**  
**WARRANTY**  
**INSTALLATION & MAINTENANCE**  
**TRIMS, TRANSITIONS & QNOSE**

tascontract.com



Additional specifications, full installation/maintenance and warranty information available online at [TASCONTRACT.COM](https://TASCONTRACT.COM).

**TAS**  
CONTRACT

TAS supply company, Inc.