

GLUE DOWN | 2 MM, 9 MIL



Patra | DJLV0401 - (NON STOCK)



Rhodes | DJLV0402 - (NON STOCK)



Capri | DJLV0403 - (NON STOCK)



Argos | DJLV0404 - (NON STOCK)

SPECIFICATIONS

Construction	Solid Luxury Vinyl
Classification	ASTMF 1700, Class III, Type B
Dimensions	7" Wide x 48" Long
Overall Thickness	2.0 mm
Wear Layer	9 mil
Finish Coat	Polyurethane with Densified Ceramic Coating
Texture	Embossed
Edge Profile	4-Sided Square Edge
Packaging	51.31 sf/ctn, 50 ctn/plt, 2565.5 sf/plt
Installation	Glue Down
Warranty	5 Yr Light Commercial, 10 Yr Multi-Family, 10 Yr Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Cypcrete Substrates

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)**

