CORNICE

PRODUCT SPECIFICATIONS

SmartGen BY Tarkett Home

SPECIFICATIONS	
Construction	Rigid Core SPC
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions (nominal)	7" wide x 48" length, 182 mm x 1220 mm
Overall Thickness	5 mm (Includes 1 mm Attached Pad)
Wear Layer Thickness	12 mil
Finish Coat	Low Gloss, Polyurethane
Texture	23.892
Edge Profile	4-Sided Micro Bevel

PACKAGING	
Coverage Per Carton	10 pcs/ctcn, 23.892 sf/ctn
Coverage Per Pallet	45 ctn/plt, 1075.14 sf/plt

INSTALLATION

Floating, Angle / Angle

WARRANTIES

25 Year Residential, 5 Year Light Commercial, 5 Year Multi-Family

TESTING

This product is designed,manufactured, and tested to meet or exceed ASTM F3261 Standards for Resilient Floor in Modular Format w/Rigid Polymeric Core. Certified to Indoor Air Quality standards, and other Environmental standards for Resilient Floor.

TEST	STANDARD	RESULT
Thickness	ASTM F386/387	Meets Requirement
Wear Layer Thickness	ASTM F410	Meets Requirement
Stain/Chemical Resistance	ASTM F925	Meets Requirement
Resistance to Heat	ASTM F1514	Meets Requirement
Resistance to Light	ASTM F1515	Meets Requirement
Residual Indentation	ASTM F1914	Meets Requirement
Size & Squareness	ASTM F2055	Meets Requirement
Dimensional Stability	ASTM F2199	Meets Requirement
Dimensional Stability W/Exposure to Heat	ISO 23999	Meets Requirement
Determination of Geometrical Element	ISO 24337	Meets Requirement
Static Coefficient Polished Surface	ASTM D2047	Meets Requirement
Flammability/Radiant Flux	ASTM E648	Meets Requirement
Static Load	ASTM F970	Meets Requirement
Smoke Density	ASTM E662	Meets Requirement
Indoor Air Quality	FloorScore Certification	Certification # SCS-FS-08362

Additional Specifications, Full Installation Instructions & Warranty Information Available at tascontract.com

TAS CONTRACT
A division of T&A supply company, Inc.