ACCLAIM



Anti-Microbial + Anti-Scratch

ABA SPC 4.5 MM, 12 MIL

Construction	ABA Rigid Core, Stone Polymer Composite	
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B	
Dimensions	7.25" Wide x 48" Long, 183 mm x 1220 mm	
Overall Thickness	4.5 mm (includes 1 mm pad)	
Attached Pad	1 mm Acoustical Pad	
Wear Layer	12 mil	
Finish Coat	Anti-Microbial & Anti-Scratch	
Texture	Embossed	
Edge Profile	4-Sided Painted Bevel	
Packaging	28.84 sf/carton - 55 cartons/pallet - 1586.2 sf/pallet	

Installation & Maintenance

Angle / Angle, Float

Expansion & Transition: 1/4" Expansion required at perimeter and at all vertical surfaces. Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor

Test Method & Requirements			
Resilient Floor in Modular Format	ASTM F3261	Pass	
Thickness (with Pad)	ASTM F386/ (387)	Pass	
Wear Layer Thickness	ASTM F410	Pass	
Stain/Chemical Resistance	ASTM F925	Pass	
Resistance to Heat Color Change	ASTM F1514	Pass	
Resistance to Light Color Change	ASTM F1515	Pass	
Residual Indentation	ASTM F1914	Pass	
Size & Squareness	ASTM F2055	Pass	
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass	
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass	
Determination of Geometrical Characteristics	ISO 24337	Pass	
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard	
Static Load Limit	ASTM F970	Pass>250 LBS	
Flammability/Radiant Flux	ASTM E648	Class I	
Smoke Density	ASTM E662	Pass	
Impact Insulation Class IIC	ASTM E492*		
Sound Transmission Class STC	ASTM E90*		
*The fleering assembly dietates IIC STC LIIIC and Low IIC society contact your			

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

FloorScore Certificate # SCS-FS-05909

Hydrophobic Antimicrobial Surfaces

ASTM E2180-18

Reduction % >99.9



Phthalate-Free
















Warranty

5 Yr Light Commercial, 5 Yr Multi-Family, 25 Yr Residential

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round
QNose Stair Nosing

