

# CORNICE



SPC | 5.0 MM, 12 MIL



**Peak** | NFRCU0102



**Belle** | NFRCU0106



**Bridger** | NFRCU0108



**Mammoth** | NFRCU0107



**Trail** | AGRC0105\*



**Incline** | AGRCU0101\*



**Alpine** | AGRCU0103\*

\*Non-Stock Colors  
Available through our  
Platforms Program.  
Minimum QTY Applies.

## SPECIFICATIONS

Construction	SPC Rigid Core, Stone Polymer Composite
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7" wide x 48" long
Overall Thickness	5 mm (Includes 1 mm pad)
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	4-Sided Micro Bevel
Packaging	26.26 sf/ctn - 50 ctn/plt - 1313 sf/plt
Installation	Angle / Angle, Float
Warranty	5 Yr Light Commercial, 5 Yr Multi-Family, 25 Yr Residential

## INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 3/16" in 10'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE**



Additional specifications, full installation/maintenance and warranty information available online at [TASCONTRACT.COM](https://TASCONTRACT.COM).



TAS supply company, Inc.