

# CRUISER

2.5 MM, 12 MIL



**Yacht** | CTLV0201



**Clipper** | CTLV0202



**Catamaran** | CTLV0203



**Sloop** | CTLV0205



**Skipjack** | CTLV0206



**Monitor** | CTLV0207

## SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 60" Long, 185 mm x 1524mm
Overall Thickness	2.5 mm
Wear Layer	12 mil
Finish Coat	UV Ceramic Bead
Texture	Embossed
Edge Profile	Soft Rolled
Packaging	54.625 sf/carton - 40 carton/pallet - 2185 sf pallet
Installation	Glue Down
Recommended Adhesive	WF Taylor: Pinnacle, Dynamic or Resolute
Warranty	5 Yr Light Commercial, 5 Yr Multi-Family, 20 Yr Residential

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F, RH Between 35% - 55%
- Do not net or compression fit
- Minimum 3500 PSI for Concrete/Gypsum
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8" in 6'

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS: [QNOSE](#)**



Additional specifications, full installation instructions & warranty information available online at [tascontract.com](https://tascontract.com)