SPARTA

EVC | 8.0 MM, 20 MIL

Construction	Premium Engineered Vinyl Core Plank	
Classification	ASTM F3261, Class 1, Type B, Grade 1, Class B	
Dimensions	Plank: 7" Wide x 48" Long Tile: 12" Wide x 24" Long	
Overall Thickness	8.0 mm (Includes 1.5mm Premium Pad)	
Attached Pad	1.5 mm Premium Pad	
Wear Layer	20 mil	
Finish Coat	Anti-Microbial Anti-Scratch	
Texture	Embossed	
Edge Profile	Plank: Micro Bevel Tile: Painted Bevel	
Packaging	19.375 sf/ctn - 66 ctn/ptl - 1278.8 sf/plt	

Installation & Maintenance

Angle/Angle

Expansion & Transition: 1/4" Expansion required at perimeter and at all vertical surfaces. Transition required for rooms larger than 50' W x 50' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor

Test Method & Requirements		
Resilient Floor in Modular Format	ASTM F3261	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Stain/Chemical Resistance	ASTM F925	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2055	Pass
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass
Dimensional Stability w/Exposure to Heat	ISO 23999	Pass
Determination of Geometrical Characteristics	ISO 24337	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	
4-1 (1		

 * The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

FloorScore SCS Certified Phthalate-Free
















Warranty

10 Year Light Commercial, 10 Year Multi-Family, Lifetime Residential.

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round

<u>ONose</u> Stair Nosing

