

**1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1. **Proprietary Product:** Luxury vinyl floor covering with Tarkett's Techtonic polyurethane comes in tile and plank form. Suitable for commercial working environments and offices:

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916  
 30000 Aurora Rd.  
 Solon, Ohio 44139  
 Web: www.tarkett.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett iD Latitude is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 20 mil PVC wear layer. Techtonic polyurethane coating technology is super tough; resisting scratching, abrasions, scuffing and staining to ensure your floor look nicer, longer.

1.3.2. **Characteristics:**

- Finish:** Techtonic
- Edge treatment:** Square Edge
- Wearlayer Thickness:** .020" (0.5 mm)
- Overall thickness:** 0.120" (3.0 mm)
- Designs:** 22 Wood, 14 Abstract, 8 Stone/Concrete

1.3.3. **Tile/Plank size and Packaging:**

Size	6" x 36" (15.2cm x 91.4cm)	6" x 48" (15.2cm x 121.9cm)	18" x 18" (45.7cm x 45.7cm)	12" x 24" (30.5 cm x 61.0 cm)
Availability	Abstract	Wood	Abstract; Stone & Concrete	Stone & Concrete
Planks per Ctn.	24	18	20	18
Sq. Ft. per Ctn.	36 (3.34 m <sup>2</sup> )	36 (3.2 m <sup>2</sup> )	45 (4.18 m <sup>2</sup> )	36 (3.34 m <sup>2</sup> )
Lbs. per Ctn.	36 (16.33 kg)	36 (16.33 kg)	47 (21.32 kg)	36 (16.33 kg)
Ctns. per Pallet	60	72	52	60

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.1. **Tile material** – Meets ASTM F1700, Class III, Type B performance standards for solid vinyl floor tile
- 2.2. **Wear layer thickness:** 20 mil
- 2.3. **Residual Indentation** (ASTM F1914): Passes
- 2.4. **Static coefficient of friction** (ASTM D2047):  $\geq 0.5$  SCOF, ADA compliant
- 2.5. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005$  inches
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514):  $\Delta \sum \leq 8.0$
- 2.8. **Resistance to Light** (ASTM F1515):  $\Delta \sum \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Flammability** (ASTM E648, CRF):  $\geq 0.45$  W/cm<sup>2</sup> (Class 1)
- 2.11. **CAN/ULC S102.2:** FSV 140 / SDV 445

**3. INSTALLATION**

See iD Latitude Luxury Vinyl Tile and Plank installation instructions for complete details.

3.1. **Adhesives:**

**Tarkett RollSmart Adhesive:**

Coverage: 350 – 400 sq. per gallon  
 (3/8" Nap Paint Roller used with a paint tray)

**Tarkett 959 Vinyl Tile Adhesive Coverage:**

Porous Substrate: 150-175 sq. ft. per gallon  
 Non-porous: 250-300 sq. ft. per gallon

**Tarkett 959HM High Moisture Substrate Adhesive**

Porous Substrate: 125-150 sq. ft. per gallon  
 Non-porous: 250-300 sq. ft. per gallon

**LVT Rollable**

Coverage: 350 – 400 sq. per gallon  
 (3/8" Nap Paint Roller used with a paint tray)

**Tarkett 975 Two-Part Urethane Adhesive**

Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

**Tarkett 996 Two-Part Epoxy Adhesive**

Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

**4. AVAILABILITY AND COST**

Available through Tarkett retailers nationwide.

**5. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to iD Latitude Maintenance Instructions for complete maintenance details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
 Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. WARRANTY**

Limited 20-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.