


AN EVOLUTION IN DESIGN. FLOORING FOR A NEW GENERATION.

High Street™

LUXURY VINYL FLOORING



ARIA | IRON 1 60083

A vinyl sheet flooring collection designed with Main Street in mind.

High Street™ offers the best of both worlds – the durability needed for light commercial applications and the stylish designs to suit any decor.

With the Techtonic™ Technology protective coating, you'll get increased durability and better performance to keep your floor looking better and lasting longer. In controlled lab tests, High Street™ outperformed the market leader with:

- **More scratch resistance**
- **More stain resistance**
- **25% more abrasion resistance**

High Street™ is not only functional, it's also stylish. Whether you want a modern and sleek aesthetic, a cozy and welcoming feel, or anything in between, we have options to suit any taste.



MAIN STREET



WATERPROOF



DURABLE



CLEANS EASILY



DIMENSIONAL STABILITY

 **Tarkett**
Home

High Street™

LUXURY VINYL FLOORING



60001 | Oslo
Pewter
48" x 72" DNR



60011 | Corbin
Latte
36" x 72" DNR



60021 | Markham
Wheat
36" x 36", 18" Drop, DNR



60031 | Ozart
Greige
36" x 36", 18" Drop, REV



60041 | Rowell
Bisque
36" x 72" DNR



60051 | Sedwick
Chai
36" x 72" DNR



60052 | Sedwick
Kobicha
36" x 72" DNR




60061 | Monroe
Sunkiss
48" x 72", Drop 24", DNR



60062 | Monroe
Chestnut
48" x 72", Drop 24", DNR



60071 | Strata
Cashmere
36" x 36" DNR



60072 | Strata
Madras
36" x 36" DNR



60081 | Aria
Glacier
36" x 36", Drop 18", DNR



60082 | Aria
Lunar
36" x 36", Drop 18", DNR



60083 | Aria
Iron
36" x 36", Drop 18", DNR



60091 | Baxton
Limestone
36" x 72" DNR



60092 | Baxton
Earth
36" x 72" DNR

Specifications	
Series	60XXX
Nominal Total Thickness	80 mils (0.08"/2.03mm)
Wear Layer Thickness	20 mils (0.02"/0.51mm)
Wear Layer Finish	Urethane (Low Gloss), Techtonic™ Technology
Width	12' (3.6m)
Standard Roll Size	100 sq. yd. (83.61 m ²)
Weight per Sq. Yd.	4.81 lbs. (2.18 kg)
ASTM F1303	Type I, Grade 1, Class C
ASTM F925 (Stain Resistance)	Passes
ASTM D2047 (Slip)	>0.5
ASTM E648 (Fire)	>.45 W/cm ²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	Passes
ASTM F970 Static Load Limit	175 lbs./sq. in. (12.3 kg/cm ²)
ASTM F1514 (Heat Stability)	Δ E < 8
ASTM F1515 (Light Stability)	Δ E < 8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 13 dB
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One™
Seam Sealer	Tarkett DT-65 Seam Sealer (Low Gloss)
HUD/FHA Minimum	Meets Wearlayer Thickness
FloorScore® Certification	SCS-FS-02746
CERTIFIED asthma & allergy friendly ® by Allergy Standards Ltd and the Asthma and Allergy Foundation of America (AAFA)	Certificate AAFC: 1880/16/05/01/2066

High Street™ floors are built to last, making it the ideal floor exclusively for Main Street customers.

DISTRIBUTED BY



Connect with us @ TarkettHome



Scan this code to visit <https://tascontract.com/collection/high-street/>



The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of ALLERGY STANDARDS LTD and the ASTHMA AND ALLERGY FOUNDATION OF AMERICA.

For more accurate color and pattern representation, we suggest you visit an authorized Tarkett Home dealer to view an actual product sample.