

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl that can be heat welded. Suitable for Residential and Light Commercial environments.

### 1.2 **Manufacturer:**

Tarkett North America                      Phone:     (800) 899-8916  
 30000 Aurora Rd.                                 (440) 543-8916  
 Solon, Ohio 44139  
 Web: [www.tarkett.com](http://www.tarkett.com)

### 1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho-phthalate free, virgin raw materials.

### 1.3.2 **Characteristics:**

**Construction:** Urethane Topcoat Sealed (Low Gloss)

**Series:** 60000

**Overall Thickness:** 0.080" (2.03 mm)

**Wearlayer Thickness:** 0.020" (0.51 mm)

**Width:** 12' (3.6 m)

**Maximum Roll Size:** 100 yd<sup>2</sup> (83.6 m<sup>2</sup>)

**Weight per Square Yard:** 4.81 lbs. (2.18 kg)

## 2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 1, Class C

2.2 **Slip Resistance:** ASTM D2047 >0.5

2.3 **Flexibility:** ASTM F137 Passes

2.4 **Static Load Limit:** ASTM F970 175 lbs./in<sup>2</sup> (12.3 kg/cm<sup>2</sup>)

2.5 **Heat Stability:** ASTM F1514 ΔE<8

2.6 **Light Stability:** ASTM F1515 ΔE<8

2.7 **Sound Reduction:** ASTM E2179 ΔIIC 13 dB

2.8 **Stain Resistance:** ASTM F925 Passes

2.9 **Fire Performance:** ASTM E648 >0.45 W/cm<sup>2</sup>

2.10 **Smoke Density:** ASTM E662 <450

2.11 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness

2.12 **FloorScore® Certification:** SCS-FS-02746

2.13 **Asthma and Allergy Certified:** AAFC: 1155/11/05/01/2066

## 3. INSTALLATION

See FiberFloor installation instructions found at [www.tarkett.com](http://www.tarkett.com) for complete details.

### 3.1 **Methods:**

Releasable

Permanent

Floating Glueless

### 3.2 **Adhesive:**

**Tarkett Qbond One**

Releasable - Medium Nap Roller

Permanent - 1/32" x 1/16" x 1/32" trowel

### 3.3 **Seaming:**

**Seam Sealer:** Tarkett DT-65 (Low Gloss)

**Heat Welding**

## 4. AVAILABILITY AND COST

Available through Tarkett Distributors and Retailers.

## 5. MAINTENANCE

See Residential Maintenance instructions found at [www.tarkett.com](http://www.tarkett.com) for complete details.

## 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical Support at (888) 639 8275, or E-mail [Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

## 7. WARRANTY

LIFETIME LIMITED RESIDENTIAL WARRANTY

Aquaguard® 2 year "No Questions Asked" Warranty

15 YEAR LIGHT COMMERCIAL WARRANTY



**ORTHO-PHTHALATE FREE**

DISTRIBUTED BY

