

# SPECMASTER 2.0 MM



GLUE DOWN | 2.0 MM | 12 MIL

Construction	Solid Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions	7.25" Wide X 48" Long
Overall Thickness	2.0 mm
Attached Pad	N/A
Wear Layer	12 mil
Finish Coat	Low Gloss, UV Ceramic Coating
Texture	Embossed
Edge Profile	Rolled Edges
Packaging	58.74 sf/ctn, 45 ctn/plt, 2643 sf/plt

## Installation & Maintenance

Glue Down

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Wax, Neutral PH cleaner, such as WF Taylor Fresh Floors


Recommended Adhesive: -Dynamic, Transitional Pressure Sensitive, firm set  
-Pinnacle, Premium Transitional Pressure Sensitive, hard set

## Test Method & Requirements

Solid Vinyl Floor Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2199	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass

## Health & Environmental

FloorScore SCS Certified  
OrthoPhthalate Free



## Warranty


10 Yr Light Commercial, 10 Yr Multi-Family, 25 Yr Residential

## Accessories


[QNose](#) Stair Nosing

## Layout Options:


NOT TO SCALE




HERRINGBONE




TRIPLE HERRINGBONE



FIVE PLANK PARQUET



ASHLAR



STAGGER

