



CERIALE
133NACAK1VKW 0

White stained Scandinavian Ash floor with color variation and matte finish.

GOTHA
133N18EL50KW 0

Bright European Maple floor with silk matte finish with light-brown grain.

VAILA
133NACAK50W 0

Silk matte finished Scandinavian Ash floor with color variation, may have knots.

LECCO
133NABEK50W 0

Clean silk matte finished European Oak floor with minor color variations and without knots.

Areas of application and special characteristics

Kährs 13 mm product is designed and suitable both for residential and commercial applications.

- Dimensionally stable due to climate-controlled production processes.
- Kährs Woodloc® 5S joint.
- Quick and simple installation because of joint design and precision manufacturing.
- High-quality wood floors that last for many years.
- Natural and unique look.
- Pre-finished with UV-cured finish, making the floors durable and easy to clean.

Construction

- All 13 mm boards consist of three layers with Kährs Woodloc® 5S joint on all four sides.
- Surface layer consists of sawn strips.
- Middle layer consists of solid pine strips.
- Bottom layer of spruce veneer.

Thickness of the surface layer

- Approx. 2.5 mm.

Surface treatment

- Pre-finished (for dry areas subject to normal wear), with UV-cured acrylic-based satin finish (approx. 30° Gardner) or matte finish (approx. 10° Gardner). The finish is free from solvents and formaldehyde. It is durable and preserves the wood's natural character.



NATURE
133NACER50CKW 0

A clean Red Oak floor with minor color variations, silk matte finish, small knots.

PIMA
133NABEK7CUW 0

European Oak floor with small color variations and with an orange/red highgloss stain. May have small knots.

BISBEE
133NABEK5MUW 0

European Oak floor with a brown stain, moderate color variations, minor knots, and a silk matte finish.

SUPAI
133NABEK5LUW 0

Dark brown European Oak floor with color variation and silk matte finish. May have knots.

Requirements for the subfloor

The subfloor must be firm, flat, and free from moisture and debris. Please see detailed subfloor requirements and preparation procedures in the Kährs Professional Installation Guides that are available for download from our web site at www.kahrs.com.

Maintenance

Detailed information about maintenance is described in our Floor Care Guide and Guarantee. Download it from our web site at www.kahrs.com.

Residential Warranty

Lifetime structural
25 year wear-through

Moisture content

Moisture content when delivered: 7%.

Weight per carton

54 lbs.

Packaging

- Protective corrugated cardboard edging (100% recycled paper).
- Protective PE sheeting (recycled).

Pack contents

Width	Length	Quantity	Ft ²
7 7/8"	95 3/8"	7	36.598