

# MONUMENT

## LAMINATE | 8 MM + 2.0 MM PAD

Construction	Water Resistant Core Laminate
Classification	EN 13329
Dimensions	9.5" Wide x 60" Long
Overall Thickness	10 mm (includes 2.0 mm EVA Pad)
Attached Pad	2.0 mm EVA Pad
Wear Surface	AC4 Rated
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	31.31 sf/ctn, 44 ctn/plt, 1377.6 sf/plt

### Installation & Maintenance

Angle/Angle

Transition: Transition required for rooms larger than 66' W x 66' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor


### Test Method & Requirements

Standard Laminate	EN 13329	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Squareness of Element	ANNEX A	Pass
Height Difference of Element	ANNEX B	Pass
Opening Between Element	ANNEX B	Pass
Tabor Abrasion	ANNEX E	Pass
Large Ball	ANNEX F	Pass
Small Ball	ANNEX F	Pass
24 Hour Thickness Swelling	ANNEX G	Pass
Resistance to Staining	EN 438	Pass
HPLC Gradient Chemical Analysis		Pass
Pull Test		Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

\*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

### Health & Environment

FloorScore SCS Certified  
GreenGuard Gold  
Adamantine Protection



### Warranty

15 Yr Light Commercial, 15 Yr Limited Multi-Family, Lifetime Residential, 80 hour Topical

### Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round

[QNose](#) Stair Nosing

### Layout Options:

