

GLUE DOWN | 5 MM, 20 MIL



Bandera | CTLV0301



Bannak | CTLV0302



Grafton | CTLV0303



Talon | CTLV0304



Oatman | CTLV0305



Oxridge | CTLV0306



Bodie | CTLV0307

SPECIFICATIONS

Construction	Solid Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions	7.25" Wide x 60" Long
Overall Thickness	5 mm
Wear Layer	20 mil
Finish Coat	Low gloss, UV Ceramic wearlayer
Texture	Embossed
Edge Profile	Soft Rolled
Packaging	24.278 sf/ctn, 45 ctn/plt, 1902.5 sf/plt
Installation	Glue Down
Warranty	15 Year Light Commercial, 15 Year Multi-Family, Lifetime Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Gypcrete Substrates

Read Complete Instructions Before Installing



tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
[QNOSE](#)

